

Stuffing-Box-Packing Typ 2017

Material composition:

Diagonally braided from gPTFE-yarn (PTFE with incorporated graphite), reinforced at the corners with continuous Aramid yarn, lubricated with silicone oil.

Properties:

Style 2017 is a high performance multi-yarn packing, which combines the advantages of the supple gPTFE material with those of tough and durable Aramid. This results in reduced shaft-wear and better thermal conductivity than standard Aramid packings.



Application areas:

Multi-purpose packing, particularly well suited for use in piston-pumps, mixers, stirrers, reactors, for industrial and chemical process valves, good for high pressure applications.

Application media:

Can be used with a wide variety of media including abrasive ones: cold and hot water, steam, solvents, oils, greases, diluted acids and lyes, brine, sewage etc.

Benefits:

TEADIT style 2017 is particularly well suited for difficult sealing applications, i.e. with high pressures or abrasive media, such ensuring longer service life. Combines exceptional extrusion resistance and high mechanical strength with good chemical and thermal stability.

Not suitable for:

Highly concentrated acids and lyes, alkali metals, fluorine and fluorine compounds at high temperatures.

Temperature:	- temp.:	+ temp.:		pH:	2-12
(°C)	100	280		Density:(g/cm³)	1,5
Pressure:	rotating:	reciprocating:	static:	v:	
(bar)	30	200	200	(m/s)	20

TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20
e-mail: mail@teadit-europe.com

TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911
I-25030 Paratico Fax: +39 - 035 - 913060
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

