

## Stuffing-Box-Packing Typ 2026

### Material composition:

Diagonally braided from textured glass-fibre yarn, impregnated throughout with PTFE-dispersion, silicone-free break-in lubricant.

### Properties:

Very dense and supple packing, good chemical resistance.

### Application areas:

TEADIT style 2026 is recommended for use in rotary and reciprocating pumps, valves, mixers and agitators etc. in the pulp- and paper, petroleum, chemical and food industry, in sugar mills and water treatment plants.

### Application media:

Style 2026 can be used with water, steam, solvents, oils, most chemicals, mild acids and lyes, etc.



### Benefits:

Style 2026 is a multi-service packing suitable for a wide variety of applications throughout a plant.

### Not suitable for:

Concentrated acids and lyes, oxygen.

<b>Temperature:</b>	<b>- temp.:</b>	<b>+ temp.:</b>	<b>pH:</b>	3-12
(°C)	40	280	<b>Density:(g/cm<sup>3</sup>)</b>	2
<b>Pressure:</b>	<b>rotating:</b>	<b>reciprocating:</b>	<b>v:</b>	
(bar)	15	20	(m/s)	8
		<b>static:</b>		
		150		

**TEADIT INTERNATIONAL PRODUKTIONS GMBH**  
 Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0  
 A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20  
 e-mail: mail@teadit-europe.com

**TEADIT ITALIA S.p.A.**  
 Via Vanzago 13 Tel.: +39 - 035 - 924911  
 I-25030 Paratico Fax: +39 - 035 - 913060  
 e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

