Product information



3/05.08.98

Stuffing-Box-Packing Typ

prev.no. 7000

Material composition:

Diagonally braided from a blue synthetic yarn, impregnated throughout with PTFE-dispersion, lubricated with silicone oil.

Properties:

TEADIT style 2700 is a good general service pump- and valve packing. High thermal and chemical resistance coupled with good mechanical strength. The low coefficient of friction of this supple packing prevents shaft wear.

Application areas:

Style 2700 can be used for demanding applications in rotary and piston pumps, mixers and stirrers, sliders and valves in a wide variety of different industries.

Application media:

Style 2700 covers a pH-range of 0 - 12 and can be used with water, steam, brine, acids, diluted alkalis, chemicals, solvents, petroleum derivatives etc.



Benefits:

Flexible and hard-wearing all-round packing, does not damage shafts or spindles, non-contaminating, high mechanical strength - resists high pressures and extrusion.

Not suitable for:

Polar solvents, concentrated alkalis, highly oxidizing agents, oxygen.

Temperature:	- temp.:	+ temp.:		pH:	0-12
(°C)	100	260		Density:(g/cm³)	1,5
Pressure:	rotating:	reciprocating:	static:	v :	
(bar)	25	25	200	(m/s)	15

TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str. 10 Tel.: +43 - 5372 - 64020 - 0 A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20 e-mail: mail@teadit-europe.com

TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911 I-25030 Paratico Fax: +39 - 035 - 913060 e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.



